

NORDSTAR


inverter

Floor Standing
the secret of cool summers



15
kW

17
kW



4D Airflow Experience

4-Dimensional cooling with horizontal and vertical swing action ensuring better airflow while giving uniform cooling.



Long Distance Airflow 18m

Achieving coolness throughout the room, extending up to 18 meters, for enhanced comfort and coverage.

Easy to install

50m pipe length

30m height diff.

Remote control

Heat Pump



DC Motor



AS Fan blade



R32

Panasonic
compressor

Outdoor Water-proof Class **IPX4**

Specially designed for social spaces, restaurants, hotel receptions, etc.

MODEL	INVERTER AP-48000BTU R32	60000BTU R410
Code	045619-209	045619-210
Rated Voltage	380 V / 3 ph	380 V / 3 ph
Cooling Capacity Btu/h	51521	58004
Cooling capacity kW	15,1 (6,5-15,5)	17
Heating capacity kW	15,2(5-16)	17,5
SCOP/EER Cooling	6,1	2,5
SCOP/COP Heating	4	2,54
Air Flow Volume indoor/outdoor m ³ /h	2100/9000	1900/5800
Refrigerant	R32	R410
Maximum pipe length	50	50
Max installation fall m	30	30
Ambient temperature Cooling/Heating °C	16~49 / -7~30	16~49 / -7~30
Indoor dimension/weight mm / kg	580x1925x400 / 52	580x1925x400/54
Outdoor dimension/weight mm / kg	940x1320x340 / 94	940x1320x340 / 102